

TECHNICAL SPECIFICATION

PARAMETER	SPECIFICATION
MODEL NAME	ODU-501
POWER SUPPLY	230VAC AT 50HZ
SYSTEM	MICRO - CONTROLLER BASED
OPERATION	PRESET MODEL
ACCURACY CLASS	0.5
DISPLAY1	1" LCD FOR RUPEE DISPLAY
DISPLAY2	1" LCD FOR QTY DISPLAY IN ML
DISPLAY 3	16X2 DISPLAY WITH 10 DIGIT FOR LITRES AND 3DIGIT FOR ML
LEAST COUNT	5 ML
MINIMUM MEASURED QTY	10 ML
MAXIMUM MEASURED QTY	1000 ML (FOR 2T ENGINE OIL) 5000 ML (FOR 4T ENGINE OIL)
INDICATIONS	LED , DISPLAY AND BUZZER
SWITCHES	MEMBRANE KEYS
OUTPUT HOSE	4 METER HYDRAULIC HOSE WITH OIL GUN*
MINIMUM FLOWRATE	500 ML PER MINUTE*
DIMENSIONS(LXWXH)IN MM	(540X385X1350)
OPTIONS AVAILABLE	SINGLE/DOUBLE SIDE CONTROL PRINTER OPTION

APPLICATION AREA: PETROL STATION/ CNG GAS STATION / FUEL STATION / INDUSTRIES/ AUTOMOTIVE SECTOR & GARAGES

*The above mentioned specifications are subjected to change without prior notice

WHY USE ICON EMBEDDED CONTROLS MAKE DIGITAL ENGINE OIL DISPENSER

- SAVES MONEY FOR BOTH BUYER AND SELLER
- SAVES ENVIRONMENT BY REDUCING PLASTIC USAGE
- ALMOST ZERO SPILLAGE WHILE DISPENSING
- PRECISED VOLUME DISPENSED
- RUPEE PER LITRE CAN BE SECURELY SET
- DISPLAYS TOTAL VOLUME DISPENSED IN LITRES & ML AND SUB TOTAL VOLUME DISPENSED IN LITRES & ML
- BATCH OR SHIFT WISE VOLUME CAN BE ERASED
- APPROVED BY LEGAL METROLOGY

APPROVAL MARK IND/09/20/657

SUITABLE TO DISPENSE
VARIOUS OIL GRADES &
BRANDS INCLUDING

SERVO **MAK**
WORLD CLASS LUBRICANTS LUBRICANTS

HP
RACER
POWER TO PERFORM

Shell Lubricants

DIGITAL 2T ENGINE OIL DISPENSER

SINGLE SIDE OPERATION



DOUBLE SIDE OPERATION



DIGITAL 2T ENGINE OIL DISPENSER WITH THERMAL PRINTER



DIGITAL 4T ENGINE OIL DISPENSER WITH THERMAL PRINTER



MANUFACTURED BY:
ICON EMBEDDED CONTROLS

374/2, JOTHINAGAR 2ND STREET,
RAMANUJAM NAGAR EXTN,
UPPILIPALAYAM POST,
COIMBATORE, TAMILNADU - 641015.

PHONE : +91422-2596032

MOBILE : +91-9751456032

E-MAIL : INFO@ICONEMBEDDEDCONTROLS.COM

WWW.AUTOMOTIVEGARAGEEQUIPMENT.COM